

# LOAD CONTROLS SYSTEMS PTE LTD

Reg. No. 199601888G

A member of Tat Hong Holdings Ltd

19 Sungei Kadut Avenue. Singapore 729654. Tel: (65) 6366 6338 Fax: (65) 6366 6339

E-mail: [lcs@tathong.com.sg](mailto:lcs@tathong.com.sg) Website: <http://www.loadcontrols.com.sg>



Our Reference : SR6979A

Date : 27 August 2005

INTER-SHIP LTD

P.O. Box 613,

Kingstown,

St. Vincent & The Grenadines.

Tel : +62 778 7022572 / 7016654

Fax : +1-603-754-0191

## Calibration Report

**Equipment** : Wylie Load Moment Indication System  
**Model No.** : W2245  
**Serial No.** : 61538  
**Manufacturer** : Wylie Systems (UK)  
**Date Calibrated** : August 25, 2005  
**Model of Crane** : Hagglund (S/N : 2026)  
Boomlength 26m Deck Crane on Offshore Olympia

	Main Hoist
Angle	63°
Radius	12.3m
SWL	20ton
Load Readout	7.5ton
Test Load	7.0ton
Part of line	2


MAIN HOIST	1st LIFT	2nd LIFT	3rd LIFT
RADIUS	17.8	23.0	24.6
SWL	10	10	10
LOAD READOUT WYLIE CONTROL	1.7 tons	3.9 tons	3.5 tons
TEST LOAD	1.6 tons	4.02 tons	3.96 tons
DIFFERENCE	0.1 tons	0.53 tons	0.46 tons

Remarks : Boom Length : 26m

Calibrated By :


  
.....  
Sheik Yusof  
Service Technician

Approved By

  
.....  
Lee Ngee Huat  
General Manager



Certificate No.: SG04/00158



## TECHNICAL SPECIFICATIONS

RE : 20 Ton General Purpose Crane

Regarding to your enquiry for second hand crane, we herewith are pleased to forward you of the technical specification of the crane.

Item 1 – Hydraulic Recond General Purpose Crane --- ( 1 set )

### *Crane specification as follows*

Hoisting Capacity SWL	:	20	Tons @ 26 Meter @ 2 fall
Hoisting Capacity	:	40	Tons @ 13 Meter @ 4 fall
Hoisting Speed	:	40	m/min ( at 0 - 8 tonnes )
	:	20	m/min ( @ 0 - 20 tons )
	:	10	m/min ( @ 0 – 40 tons )
Lifting height	:	50	meter
Luffing Time	:	40	sec
Slewing Speed	:	1.2	rev/min
Jib radius, max.	:	26	m
Jib radius, min.	:	3.5	m
Main Power Supply	:	380V, 50Hz	
Certificate	:	Maker Certificate	
Make	:	Macgregor - Hagglunds (Europe)	